



CAPACITY
5 Tonne (50 MHa Y-R1/1)
LIFT SPEED : 13.6/2.0 mpm.

1/1

CAPACITY
10 Tonne (100 MHa Y-R2/1)
LIFT SPEED : 6.8/1.0 mpm.

2/1

CAPACITY
20 Tonne (200 MHa Y-R4/1)
LIFT SPEED : 3.4/0.5 mpm.

4/1

TYPE	DRUM		ROPE	LIFTING HEIGHT				WEIGHT			DIMENSION in mm.					
	ROPE PCD.	PITCH		ROPE ϕ mm.	1/1 m.	2/1 m.	4/1 m.	1/1 Kg	2/1 Kg	4/1 Kg	'A' mm.	'B' mm.	'D' mm.	'E' mm.	'E' mm.	
Y	ϕ mm.	mm.	mm.	1/1	2/1	4/1	1/1	2/1	4/1	'A'	'B'	'D'	'E'	'E'		
				m.	m.	m.	Kg	Kg	Kg	mm.	mm.	mm.	mm.	mm.	mm.	
				24	12	6				1198	658	470	235	118		
				40	20	10				1518	978	784	392	196	62	193
MHa				60	30	15				1918	1378	1175	587	294		250

COPYRIGHT

THIS DESIGN & PRINT IS THE PROPERTY OF HYDROMECH PVT.LTD. AND MUST NOT BE COPIED IN ANY FORM.

HYDROMECH
A.C.N. 060 136 313

HOIST ASSEMBLY
MALLAWA MODEL MHa
FOOT MOUNTED

REV.	DESCRIPTION	BY	DATE	DATE	DRAWING NUMBER
A	HOOK H/R REVISED	MB	22.5.98	28/8/96	A-H-797A
				CHK'D	SHEET SIZE
				GLH	A3
				SCALE	
				1 : 20	